This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · 0 Comments
2021/08/20 03:18 · prokushev · 0 Comments

DosMkDir2

This call creates a subdirectory that has extended attributes associated with it.

Syntax

```
DosMkDir2 (DirName, EABuf, Reserved)
```

Parameters

- DirName (PSZ) - input : Address of the ASCIIZ directory path name, which may or may not contain a drive specification. If no drive is specified, the current drive is assumed.

DosQSysInfo is called by an application during initialization to determine the maximum path length allowed by OS/2.

- EABuf (PEAOP) - input/output: Address of the extended attribute buffer, which contains an EAOP structure.
- Reserved (ULONG) - input: Reserved and must be set to zero.

Return Code

rc (USHORT) - return: Return code

- 0 NO_ERROR
- 3 ERROR_PATH_NOT_FOUND
- 5 ERROR_ACCESS_DENIED
- 26 ERROR_NOT_DOS_DISK
- 87 ERROR_INVALID_PARAMETER
- 108 ERROR_DRIVE_LOCKED
- 206 ERROR_FILENAME_EXCED_RANGE
- 254 ERROR_INVALID_EA_NAME
- 255 ERROR_EA_LIST_INCONSISTENT

Remarks

DosMkDir2 allows an application to define extended attributes for a subdirectory at the time of its creation.

If any subdirectory names in the path do not exist, the subdirectory is not created. Upon return, a subdirectory is created at the end of the specified path.

DosQSysInfo must be used by an application to determine the maximum path length supported by OS/2. The returned value should be used to dynamically allocate buffers that are to be used to store paths.

If a program running with the NEWFILES bit set tries to create a directory with blanks immediately preceding the dot on a FAT drive, the system rejects the name. For example, if c: is a FAT drive, the name “file .txt” is rejected and the name “file.txt” is accepted.

Bindings

C

```
typedef struct _GEA {       /* gea */
  BYTE cbName;             /* name length not including NULL */
  CHAR szName[1];          /* attribute name */
} GEA;

typedef struct _GEALIST {   /* geal */
  ULONG  cbList;           /* total bytes of structure including full list */
  GEA list[1];             /* variable length GEA structures */
} GEALIST;

typedef struct _FEA {       /* fea */
  BYTE fEA;                /* flags */
  BYTE cbName;             /* name length not including NULL */
  USHORT cbValue;          /* value length */
} FEA;

typedef struct _FEALIST {   /* feal */
  ULONG  cbList;           /* total bytes of structure including full list */
  FEA list[1];             /* variable length FEA structures */
} FEALIST;

typedef struct _EAOP {      /* eaop */
  PGEALIST fpGEAList;      /* general EA list */
  PFEALIST fpFEAList;      /* full EA list */
  ULONG  oError;
} EAOP;

#define INCL_DOSFILEMGR
```

```
USHORT  rc = DosMkDir2(DirName, EABuf, Reserved);

PSZ     DirName;        /* New directory name string */
PEAOP   EABuf;          /* Extended attribute buffer */
ULONG   0;              /* Reserved (must be zero) */

USHORT  rc;             /* return code */
```

MASM

```
GEA     struc
  gea_cbName      db  ?           ;name length not including NULL
  gea_szName      db  1 dup (?)   ;attribute name
GEA     ends

GEALIST     struc
  geal_cbList     dd  ?       ;total bytes of structure including full list
  geal_list       db  size GEA * 1 dup (?) ;variable length GEA structures
GEALIST     ends

FEA   struc
  fea_fEA         db  ? ;flags
  fea_cbName      db  ? ;name length not including NULL
  fea_cbValue     dw  ? ;value length
FEA   ends

FEALIST struc
  feal_cbList     dd  ?       ;total bytes of structure including full list
  feal_list       db  size FEA * 1 dup (?) ;variable length FEA structures
FEALIST ends

EAOP    struc
  eaop_fpGEAList  dd  ? ;general EA list
  eaop_fpFEAList  dd  ? ;full EA list
  eaop_oError     dd  ? ;
EAOP    ends

EXTRN  DosMkDir2:FAR
INCL_DOSFILEMGR     EQU 1

PUSH@  ASCIIZ  DirName       ;New directory name string
PUSH@  OTHER   EABuf         ;Extended attribute buffer
PUSH   DWORD   0             ;Reserved (must be zero)
CALL   DosMkDir2
```

Returns WORD

Family API		
DOS	Process Manager	DosBeep DosExit DosSleep DosExecPgm
	File Manager	DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSetFileMode DosOpen DosQFileInfo DosRead DosQFileMode DosQFSInfo DosQVerify DosRmDir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSetFileInfo DosSetVerify DosWrite DosFileLocks DosSetFHandState DosNewSize DosBufReset DosQFHandState DosSetFSinfo DosShutdown
	Memory Manager	DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAllocHuge DosAllocSeg DosReallocHuge DosReallocSeg DosGetHugeShift DosCreateCSAlias
	NLS	DosCaseMap DosGetCtryInfo DosGetDBCSEv DosSetCtryCode DosGetCollate DosGetMessage DosInsMessage DosPutMessage
	Date and Time	DosSetDateTime DosGetDateTime
	Devices	DosDevConfig DosDevIOCtl DosDevIOCtl2
	Signals	DosHoldSignal DosSetSigHandler
	Misc	BadDynLink DosGetEnv DosGetMachineMode DosGetVersion DosError DosErrClass DosSetVec
KBD		KbdCharIn KbdFlushBuffer KbdGetStatus KbdSetStatus KbdStringIn KbdPeek
VIO		VioGetBuf VioGetConfig VioGetCurPos VioGetCurType VioGetPhysBuf VioReadCellStr VioReadCharStr VioScrollUp VioScrollDn VioScrollLf VioScrollRt VioScrUnLock VioSetCurPos VioSetCurType VioSetMode VioGetMode VioShowBuf VioWrtCellStr VioWrtCharStr VioWrtCharStrAtt VioWrtNAttr VioWrtNCell VioWrtNChar VioWrtTTY VioScrLock VioPopUp
Tools		BIND
Modules		DOSCALLS.DLL VIOCALLS.DLL KBDCALLS.DLL MSG.DLL
Libraries		API.LIB OS2386.LIB FAPI.LIB DOSCALLS.LIB SUBCALLS.LIB

2018/08/25 15:05 · prokushev · 0 Comments

From:
https://www.osfree.org/doku/ - **osFree wiki**

Permanent link:
https://www.osfree.org/doku/doku.php?id=en:docs:fapi:dosmkdir2

Last update: **2021/09/17 06:25**