2025/11/04 06:16 1/3 VioSavRedrawWait

This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

**Note:** This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · 0 Comments 2021/08/20 03:18 · prokushev · 0 Comments

# VioSavRedrawWait

This call notifies a graphics mode application when it must save or redraw its screen image.

## **Syntax**

VioSavRedrawWait (SavRedrawIndic, NotifyType, VioHandle)

#### **Parameters**

- SavRedrawIndic (USHORT) input : Indicates which events the application is waiting for:
  - 0 The session manager notifies the application for both save and redraw operations.
  - 1 The session manager notifies the application for redraw operations only.
- NotifyType (PUSHORT) output : Address that specifies the operation to be performed by the application upon return from VioSavRedrawWait:
  - 0 Save screen image
  - ∘ 1 Restore screen image.
- VioHandle (HVIO) input : Reserved word of 0s.

### **Return Code**

rc (USHORT) - return:Return code descriptions are:

- 0 NO ERROR
- 421 ERROR VIO INVALID PARMS
- 422 ERROR VIO FUNCTION OWNED
- 423 ERROR VIO RETURN
- 430 ERROR VIO ILLEGAL DURING POPUP
- 436 ERROR VIO INVALID HANDLE
- 465 ERROR\_VIO DETACHED
- 494 ERROR VIO EXTENDED SG

### **Remarks**

OS/2 uses VioSavRedrawWait to notify a graphics mode application to save or restore its screen image at screen switch time. The application in the outgoing foreground session is notified to perform a save. The application in the incoming foreground session is notified to perform a restore. The application must perform the action requested and immediately re-issue VioSavRedrawWait. When an application performs a save, it saves its physical display buffer, video mode, and any other information the application needs to completely redraw its screen at restore time.

Only one process per session can issue VioSavRedrawWait. The process that first issues VioSavRedrawWait becomes the owner of the function.

A text mode application must issue VioSavRedrawWait only if the application writes directly to the registers on the display adapter. Assuming VioSavRedrawWait is not issued by a text mode application, OS/2 performs the required saves and restores.

An application that issues VioSavRedrawWait may also need to issue VioModeWait. This would allow the application to be notified when it must restore its mode at the completion of an application or hard error pop-up. Refer to VioModeWait for more information. Two application threads would be required to perform these operations in this case.

At the time a VioSavRedrawWait thread is notified, the session is in transition to/from the background. Although the session's official status is background, any selector to the physical display buffer previously obtained by the VioSavRedrawWait process (through VioGetPhysBuf) is valid at this time. The physical display buffer must be accessed without issuing VioScrLock. Since the session's official status is background, any thread waits if it issues VioScrLock with the "wait if unsuccessful" option.

An application containing a VioSavRedrawWait thread should be designed so that the process does not cause any hard errors while the VioSavRedrawWait thread is running, otherwise a system lockout may occur.

An application's VioSavRedrawWait thread may be notified to perform a restore before it is notified to perform a save. This happens if the application was running in the background the first time it issued VioSavRedrawWait. The return from this function call provides the notification. The thread that issues the call performs the save or redraw and then reissues VioSavRedrawWait to wait until its screen image must be saved or redrawn again.

## **Bindings**

#### C

```
#define INCL_VIO

USHORT rc = VioSavRedrawWait(SavRedrawIndic, NotifyType, VioHandle);

USHORT SavRedrawIndic; /* Save/redraw indicator */
PUSHORT NotifyType; /* Notify type (returned) */
HVIO VioHandle; /* Video handle */
```

USHORT rc; /\* return code \*/

#### **MASM**

```
EXTRN VioSavRedrawWait:FAR
INCL_VIO
                   E0U 1
              SavRedrawIndic ;Save/redraw indicator
PUSH
      WORD
PUSH@ WORD
              NotifyType
                             ;Notify type (returned)
              VioHandle
PUSH
      WORD
                             ; Video handle
      VioSavRedrawWait
CALL
Returns WORD
```

http://www.edm2.com/index.php/VioSavRedrawWait\_(OS/2\_1.x)

From:

http://www.osfree.org/doku/ - osFree wiki

Permanent link:

http://www.osfree.org/doku/doku.php?id=en:docs:fapi:viosavredrawwait&rev=1634193171

Last update: 2021/10/14 06:32