This is part of **Win16 API** which allow to create versions of program from one source code to run under OS/2 and Win16. Under OS/2 program can be running under Win-OS/2 if program is Windows NE executable, and with help on Windows Libraries for OS/2, if it is OS/2 NE executable. Here is a WLO to OS/2 API mapping draft

2021/09/01 04:23 · prokushev · 0 Comments

OpenDriver

Brief

Opens an installable driver.

Syntax

HDRVR WINAPI OpenDriver(LPCSTR szDriverName, LPCSTR szSectionName, LPARAM lParam);

Parameters

- **szDriverName**

Far pointer to driver name.

- **szSectionName**

Far pointer to section name in SYSTEM.INI.

- **lParam**

Additional parameter.

Return Code

Returns handle to the driver, or NULL if failed.

Notes

Installable drivers provide extended functionality beyond standard Windows API.

C Binding

```
HDRVR hDriver = OpenDriver("MYDRV", "MyDriverSection", 0);
```

MASM Binding

```
push lParam
push seg szSectionName    ; szSectionName segment
push offset szSectionName ; szSectionName offset
push seg szDriverName     ; szDriverName segment
push offset szDriverName  ; szDriverName offset
call OpenDriver
```

See also

CLOSEDRIVER, SENDDRIVERMESSAGE

From:
https://osfree.org/doku/ - **osFree wiki**

Permanent link:
https://osfree.org/doku/doku.php?id=en:docs:win16:api:user:opendriver

Last update: **2025/11/29 06:56**