

## MouClose

**Bindings:** C, MASM

This call closes the mouse device for the current session.

*MouClose* (**DeviceHandle**)

*DeviceHandle* (**HMOU**) - input Mouse device handle from a previous MouOpen.

*rc* (**USHORT**) - return Return code descriptions are:

<b>0</b>	<b>NO_ERROR</b>
385	ERROR_MOUSE_NO_DEVICE
466	ERROR_MOU_DETACHED
501	ERROR_MOUSE_NO_CONSOLE
505	ERROR_MOU_EXTENDED_SG

### Remarks

[MouClose](#) closes the mouse device for the current session and removes the mouse device driver handle from the list of valid open mouse device handles.

### C bindings

```
#define INCL_MOU

USHORT  rc = MouClose(DeviceHandle);

HMOU           DeviceHandle; /* Mouse device handle */

USHORT        rc;           /* return code */
```

### MASM bindings

```
EXTRN  MouClose:FAR
INCL_MOU           EQU 1

PUSH   WORD        DeviceHandle ;Mouse device handle
CALL   MouClose

Returns WORD
```

From:

<https://ftp.osfree.org/doku/> - **osFree wiki**

Permanent link:

<https://ftp.osfree.org/doku/doku.php?id=en:ibm:prcp:mou:close>

Last update: **2016/09/15 03:13**

