

MouFlushQue

Bindings: C, MASM

This call directs the mouse driver to flush (empty) the mouse event queue and the monitor chain data for the session.

MouFlushQue (**DeviceHandle**)

DeviceHandle (**HMOU**) - input Mouse device handle from a previous [MouOpen](#).

rc (**USHORT**) - return Return code descriptions are:

| | |
|----------|------------------------|
| 0 | NO_ERROR |
| 385 | ERROR_MOUSE_NO_DEVICE |
| 466 | ERROR_MOU_DETACHED |
| 501 | ERROR_MOUSE_NO_CONSOLE |
| 505 | ERROR_MOU_EXTENDED_SG |

C bindings

```
#define INCL_MOUSE

USHORT rc = MouFlushQue(DeviceHandle);

HMOU DeviceHandle; /* Mouse device handle */

USHORT rc; /* return code */
```

MASM bindings

```
EXTRN MouFlushQue:FAR
INCL_MOUSE EQU 1

PUSH WORD DeviceHandle ;Mouse device handle
CALL MouFlushQue

Returns WORD
```

From:
<http://www.osfree.org/doku/> - **osFree wiki**

Permanent link:
<http://www.osfree.org/doku/doku.php?id=en:ibm:prcp:mou:flushque>

Last update: **2016/09/15 03:38**

