

MouGetEventMask

Bindings: C, MASM

This call returns the current value of the mouse event queue mask.

MouGetEventMask (EventMask, DeviceHandle)

EventMask (PUSHORT) - output Address in application storage where the current mouse device driver's event mask is returned to the caller by the mouse device driver.

The *EventMask* is set by [MouSetEventMask](#), and has the following definition:

| Bit | Description |
|------|--|
| 15-7 | Reserved, set to zero. |
| 6 | Set to report button 3 press/release events, without mouse motion. |
| 5 | Set to report button 3 press/release events, with mouse motion. |
| 4 | Set to report button 2 press/release events, without mouse motion. |
| 3 | Set to report button 2 press/release events, with mouse motion. |
| 2 | Set to report button 1 press/release events, without mouse motion. |
| 1 | Set to report button 1 press/release events, with mouse motion. |
| 0 | Set to report mouse motion events with no button press/release events. |

DeviceHandle (HMOU) - input Handle of the mouse device from a previous [MouOpen](#).

rc (USHORT) - return Return code descriptions are:

| | |
|-----|------------------------|
| 0 | NO_ERROR |
| 385 | ERROR_MOUSE_NO_DEVICE |
| 466 | ERROR_MOU_DETACHED |
| 501 | ERROR_MOUSE_NO_CONSOLE |
| 505 | ERROR_MOU_EXTENDED_SG |

Remarks

Buttons are logically numbered from left to right.

C bindings

```
#define INCL_MOU

USHORT  rc = MouGetEventMask(EventMask, DeviceHandle);

PUSHORT      EventMask;      /* Event Mask word */
HMOU        DeviceHandle;  /* Mouse device handle */

USHORT      rc;           /* return code */
```

MASM bindings

```
EXTRN MouGetEventMask: FAR
INCL_MOU           EQU 1

PUSH@ WORD      EventMask      ;Event Mask word
PUSH  WORD      DeviceHandle  ;Mouse device handle
CALL   MouGetEventMask

Return WORD
```

From:
<http://www.osfree.org/doku/> - osFree wiki

Permanent link:
<http://www.osfree.org/doku/doku.php?id=en:ibm:prcp:mou:getevmask>



Last update: **2016/09/15 03:44**