VioGetAnsi

Bindings: C, MASM

This call returns the current ANSI status On/Off state.

VioGetAnsi (Indicator, VioHandle)

Indicator (**PUSHORT**) - output Address of the current ANSI status. A value of 1 indicates ANSI is active, and a value of 0 indicates ANSI is not active.

VioHandle (**HVIO**) - input This must be zero unless the caller is a Presentation Manager application, in which case it must be the value returned by VioGetPs.

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
436	ERROR_VIO_INVALID_HANDLE
465	ERROR_VIO_DETACHED

C bindings

```
#define INCL_VIO

USHORT  rc = VioGetAnsi(Indicator, VioHandle);

PUSHORT          Indicator;     /* On/Off indicator (returned) */
HVIO             VioHandle;     /* Vio handle */

USHORT           rc;            /* return code */
```

MASM bindings

```
EXTRN  VioGetAnsi:FAR
INCL_VIO            EQU 1

PUSH@  WORD    Indicator     ;On/Off indicator (returned)
PUSH   WORD    VioHandle     ;Vio handle
CALL   VioGetAnsi

Returns WORD
```

From:
http://www.osfree.org/doku/ - **osFree wiki**

Permanent link:
http://www.osfree.org/doku/doku.php?id=en:ibm:prcp:vio:getansi

Last update: **2016/09/14 10:53**