

MouClose closes the mouse device for the current session and removes the mouse device driver handle from the list of valid open mouse device handles.

### Syntax

MouClose (DeviceHandle)

### Parameters

;DeviceHandle (HMOU) - input : Mouse device handle from a previous MouOpen.

### Return Code

;rc (USHORT) - return:Return code descriptions are: \* 0 - NO\_ERROR \* 385 - ERROR\_MOUSE\_NO\_DEVICE \* 466 - ERROR\_MOU\_DETACHED \* 501 - ERROR\_MOUSE\_NO\_CONSOLE \* 505 - ERROR\_MOU\_EXTENDED\_SG

### Bindings

#### C

```
<PRE> #define INCL_MOUSE
```

```
USHORT rc = MouClose(DeviceHandle);
```

```
HMOU DeviceHandle; /* Mouse device handle */ USHORT rc; /* return code */ </PRE>
```

#### MASM

```
<PRE> EXTRN MouClose:FAR INCL_MOUSE EQU 1
```

```
PUSH WORD DeviceHandle ;Mouse device handle CALL MouClose
```

```
Returns WORD </PRE>
```

#### Mou

From:  
<https://www.osfree.org/doku/> - **osFree wiki**

Permanent link:  
<https://www.osfree.org/doku/doku.php?id=en:docs:fapi:mouclose&rev=1633614256>

Last update: **2021/10/07 13:44**



